

[54] **MODEM TELEPHONE INTERFACE CIRCUIT**

[75] Inventor: **Arthur L. Serrano**, Canoga Park, Calif.

[73] Assignee: **Novation, Inc.**, Tarzana, Calif.

[21] Appl. No.: **234,699**

[22] Filed: **Feb. 17, 1981**

[51] Int. Cl.³ **H04L 5/00**

[52] U.S. Cl. **179/2 C; 179/2 DP**

[58] Field of Search **179/1 C, 1 PC, 2 C, 179/1 SW, 2 DP, 3, 4**

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,517,137	6/1970	Ribner	179/2 DP X
3,524,935	8/1970	Gonsewski et al.	179/2 DP X
3,647,993	3/1972	Foulkes et al.	179/2 DP X
3,665,107	5/1972	Kopec et al.	179/2 DP X
3,822,364	7/1974	Lee	179/2 C
3,962,546	6/1976	Hashimoto	179/2 DP
4,009,342	2/1977	Fahrenschon et al.	179/2 DP
4,160,122	7/1979	Jacobson .	

FOREIGN PATENT DOCUMENTS

935581	10/1973	Canada	179/2 DP
987261	3/1965	United Kingdom	179/2 DP

Primary Examiner—A. D. Pellinen
Assistant Examiner—Keith E. George
Attorney, Agent, or Firm—Blakely, Sokoloff, Taylor & Zafman

[57] **ABSTRACT**

An interfacing circuit for directly coupling the handset of a telephone to a modem with provision for monitoring the data on the phone line is disclosed. The circuit may be readily connected to standard telephones. Four modes of operation are selectable by a pair of switches. The four modes of operation which may be utilized are as follows: normal phone operation, normal modem operation without the monitoring, normal modem operation with monitoring, and monitoring of data received only. In addition to allowing easy monitoring of data on the phone lines, the invention eliminates the need for a special phone to allow direct connection of a modem to a dial-up phone.

9 Claims, 2 Drawing Figures

